


Pages 1 / 3	Specifications Product: ESNRT7	
-----------------------	---	---

ESNRT7 monitor with 7" colour TFT. User friendly menu driven settings through encoder, It is used in ICU as a bedside monitor.

- Parameters are as follows,
 - ECG
 - SpO2
 - NIBP
 - Respiration
 - Temperature

1. General

Dimensions	: 230mm X 200mm X 185mm (LXBXH)
Weight	: Approx.2.7kg. with in built battery.
Display	: 7" Color monitor
Resolution	: 800 x 480 pixels
Language	: English
User Interface	: Encoder & keyboard
Alarm	: User adjustable high & low limit, Audiable and visual alarming
Trend	: 24 hrs Graphical and tabular trend of all parameter
Network	: Connectivity to central monitoring system (Panorama)

2. Power supply


Input	: 150 - 260 VAC, 50 Hz, 1 Ø.
Output	: 18V DC @ 1.2 A.
Battery	: 12 V /1.2 Ah (in built) sealed lead acid
Back-up time	: 2-3 hrs on full charge
Power consumption	: < 30 Watts
Charging Time	: 10 to 12 hours (typically)

3. Environmental

Operating Temp	: -5 °C to +45 °C
Humidity	: up to 95 % non-condensing.

4. ECG

Parameter	: HR
Frequency response	: 0.5 Hz to 35 Hz
Lead selection	: Lead I, II, III, aVR, aVL, aVF and V
Measurement HR range	: 10 to 250 bpm.

Pages 2 / 3	Specifications Product: ESNRT7	
-----------------------	---	---

Gain : 0.5, 1.0, and 2.0.
CMRR : > 90 db.
Sweep speed : 12.5, 25.0, 50.0 mm/S.
Accuracy of HR : +/- 1 bpm
Beep on every QRS detected

5. RESPIRATION

Parameter : Respiration rate
Measurement Method : Impedance between RA-LL
Measurement Range : 1 to 120 bpm
Accuracy : +/-2 bpm

6. SpO2


Parameter : SpO2%, PR, Bargraph, Perfusion index
SpO2 % Range : 0 to 100%
Accuracy : ± 2% (70~100% SpO2)
 ± 3% (35~69% SpO2)
Resolution : 1 %
Indication : Finger absent, Searching pulse
Measurement PR Range: 10 – 250 bpm
Accuracy of PR : +/- 2 bpm
Resolution of PR : 1 bpm
Probe : Adult, Pediatric, Neonate
Pitch variation change with oxygen saturation

7. NIBP

Method : Oscillometric
Range : 10 to 250
Accuracy : +/-3mmHg
Time interval : User selectable 3 min. to 250 min.
Cuff : Single tube with Velcro.
Cuff deflation : Automatic.
NIBP mode : Adult, Pediatric, Neonatal

8. TEMPERATURE

Parameter : Temperature
Measurement Range : 5 to 50 °C OR 41 to 122 °F

Pages 3 / 3	Specifications Product: ESNRT7	
-----------------------	--	---

Temperature unit : Celsius OR Fahrenheit

❖ **Settings**

- Limit setting for individual parameter
- Facility to set default settings.

❖ **Keys:**

Following hotkeys are provided for fast and easy operation

- Alarm ON / OFF
- QRS Beep ON / OFF
- Take BP
- Home
- Power

❖ **Knobs:**

- Encoder interface for browsing
- QRS beep volume knob

❖ **List of accessories for ESNRT7**

Sr.No.	Material Name	Qty.
1	ECG Cable 5 lead	1
2	SpO2 finger probe (Adult)	1
3	NIBP Cuff (with 2 meter tube of cuff) (Applicable to MPARA,MPARA7)	1
	NIBP cuff with extension (Applicable to ESNRT7,ESN7)	1
4	Temperature probe (Surface) (Applicable to ESNRT7,MPARA7)	1
5	Adapter 18V/1.2A	1
6	User Manual	1
7	Disposable Electrode	10
8	Fuse Slow blow 3A, 20mm slow blow fuse	2

* Due to our continuous product improvement programme, the specification may change without prior notice.