


<b>Pages</b> 1 / 2	<b>Specifications</b>  <b>Product: EPARA</b>	
-----------------------	--	---

EPARA is 7" colour ECG monitor. User friendly menu driven settings through encoder, It is used in ICU as a bedside monitor.

- Parameters are as follows,  
ECG

### 1. General

Dimensions	: 230mm X 200mm X 185mm (LXBXH)
Weight	: Approx.2.7kg. with in built battery.
Display	: 7" Color monitor
Resolution	: 800 x 480 pixels
Language	: English
User Interface	: Encoder & keyboard
Alarm	: User adjustable high & low limit, Audible and visual alarming
Trend	: 24 hrs Graphical and tabular trend parameter
Network	: Connectivity to central monitoring system (Panorama)

### 2. Power supply


Input	: 150 - 260 VAC, 50 Hz, 1 Ø.
Output	: 18V DC @ 1.2 A.
Battery	: 12 V /1.2 Ah (in built) sealed lead acid
Back-up time	: 2-3 hrs on full charge
Power consumption	: < 30 Watts
Charging Time	: 10 to 12 hours (typically)

### 3. Environmental

Operating Temp	: -5 °C to +45 °C
Humidity	: up to 95 % non-condensing.

### 4. ECG

Parameter	: HR
Frequency response	: 0.5 Hz to 35 Hz
Lead selection	: Lead I, II, III, aVR, aVL, aVF and V
Measurement HR range:	10 to 250 bpm.
Gain	: 0.5, 1.0, and 2.0.
CMRR	: > 90 db.
Sweep speed	: 12.5, 25.0, 50.0 mm/S.
Accuracy of HR	: +/- 1 bpm
Beep on every QRS detected	

<b>Pages</b> 2 / 2	<b>Specifications</b>  <b>Product: EPARA</b>	
-----------------------	--	---

**Settings**

- Limit setting for individual parameter
- Facility to set default settings.

❖ **Keys:**

Following hotkeys are provided for fast and easy operation

- Alarm ON / OFF
- QRS Beep ON / OFF
- Home
- Power ON / OFF

❖ **knobs:**

- Encoder interface for browsing
- QRS beep volume knob

❖ **List of accessories for EPARA**

Sr.No.	Material Name	Qty.
1	ECG Cable 5 lead	1
2	Adapter 18V/1.2A	1
3	User Manual	1
4	Disposable Electrode	10
5	Fuse Slow blow 3A, 20mm slow blow fuse	2

\* Due to our continuous product improvement programme, the specification may change without prior notice.